



Fire brigade

Liquidation
of Accidents

Industry



Eccotarp collapsible railway berm

Collapsible spill berm designed for use on railway tracks. The container is designed to protect the environment, persons and objects from hazardous leaks from trains and other rail vehicles. The special design was developed to accurately copy the track gauge as well as to function without the support of the tracks. Ideal for use during railway accidents, at railway stations, in depots, near standing loaded tanker rail cars, etc.



- ▶ Designed to accurately fit between the rail tracks
- ▶ Possibility of fitting round any object
- ▶ Quick assembly
- ▶ Easy handling
- ▶ Maximum carrying capacity 441 lb
- ▶ Volume 211 gal
- ▶ Side supports to ensure higher stability
- ▶ Optional drain hole

**Designed specifically
for railway applications**





Berm in transport shape



Can be completely unfolded to a flat surface to be washed



Folded out berm ready for final assembly



Easy handling thanks to side handles

Special design accurately fitting between EU rail gauge (any other dimension is possible on request)

There are two ways to place the tank under a train or other track vehicle: across the tracks or along them into the inner space between the tracks. Both ways passed very strict testing.



Optional drain hole

Correct anchoring of the side support



Technical details

The railway berms are self-supporting, made from PVC with a protective proofing layer (PES/PVC 1,5 Lbs/ft²). The material is oil and acid resistant (see Chemical resistance certificate in the relevant chapter at the end of catalog). Due to reinforcements in the side walls the spill berms are rigid and self-supporting. Stability is ensured by means of added external side supports.

Side handles are attached for easy handling. The spill berm can be easily and quickly unfolded to a flat surface to be washed. The bag is a standard part of the product. The berm can be optionally fitted with an optional drain hole. The maximum carrying capacity is 441 lb. The temperature range for using the berm is from -22 °F to +158 °F. The berm can be manufactured in various sizes according to individual customer requirements.

Type	Dimensions of assembled berm (d × w × h)	Dimensions in transport (disassembled) state (d × w × h)	Volume	Weight
ET RAIL	47.7 × 98.5 × 13 in	36 × 19.7 × 6.7 in	211 gal	26.5 lb
Standard accessories				
Bag				
Optional accessories at extra cost				
Ball valve D25/other				